

~~1/2 2-3~~
 SIN 09/710, 892
 Group 1772
 JJP

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-104805

(43)Date of publication of application : 23.04.1996

(51)Int.Cl.

C08L 77/00
 B32B 1/08
 B32B 27/18
 B32B 27/30
 B32B 27/34
 C08K 5/34
 F16L 11/04
 F16L 11/08

(21)Application number : 07-203270

(71)Applicant : TOKAI RUBBER IND LTD

(22)Date of filing : 09.08.1995

(72)Inventor : MURAKAMI KOYO
 ITO HIROAKI
 OMI EIICHI
 TAKAHASHI AKIHIKO
 KODAMA TSUTOMU

(30)Priority


Priority number : 06187611 Priority date : 09.08.1994 Priority country : JP

(54) FUEL HOSE AND RESIN COMPOSITION THEREFOR

(57)Abstract:

PURPOSE: To obtain an inexpensive and high-performance fuel hose free from any problem of safety during its production, and having high interlaminar adhesion strength.

CONSTITUTION: This fuel hose 1 is made up of a tubular inner layer 2 and an outer layer 3 directly laminated on the outer peripheral surface of the inner layer 2. The inner layer 2 is made of a fluororesin, and the outer layer 3 is made of a polyamide resin containing 0.5-10wt.% of a carboxylic acid 1,8- diazabicyclo[5,4,0] undecene-7 salt based of the polyamide resin.



LEGAL STATUS

[Date of request for examination]

05.12.2000

[Date of sending the examiner's decision of rejection]